

# REZSTONE

Epoxy Floor Systems

**TECHNICAL DATA**

## 5078-C 100% SOLIDS CONDUCTIVE HI-BUILD EPOXY COATING

### **Description:**

Rez-Stone 5078-C is a 100% solids hi-build epoxy coating for high indoor traffic areas, such as pedestrian walkways or factory aisles, where static-dissipating properties are needed. Rez-Stone 5078-C is ideal for a finish coating over Rez-Stone epoxy overlays and coatings systems where stain and abrasion resistance are required along with electrical conductivity. Rez-Stone 5078-C has very little odor and has excellent resistance to most common industrial cleaners and fluids.

### **Advantages:**

- ✓ Excellent conductivity
- ✓ Gloss tile -like finish
- ✓ Moisture insensitive
- ✓ Solvent free
- ✓ No VOC's

### **Limitations:**

- ✓ Minimum substrate temperature 50°F
- ✓ New concrete must be at least 28 days old
- ✓ Do not apply over wet surfaces

### **Packaging:**

Unit Size: 3 quart units, 1½ gallon units, 15 gallon units, 150 gallon units.

Coverage: 95 square feet per gallon.

### **Surface Preparation:**

Concrete surfaces must be clean and sound. Remove all dirt, laitance, grease, wax, curing compounds, and other bond-inhibiting contaminants by shot blasting, scarification, or other approved mechanical methods.

### **Mixing:**

Mix Ratio: 2 Parts A (resin) to 1 Part B (curing agent) by volume. Temperature of material must be between 60°F and 90°F at time of mixing for best application properties. Stir the Part A (resin) component before blending with curing agent. Mix two parts by volume Part A with one part by volume Part B for three minutes with low speed drill and paddle. Mix only that amount of material that can be used within its applicable pot life.

### **Application:**

Rez-Stone 5078-C can be applied directly over properly prepared and primed concrete or over Rez-Stone epoxy overlayments and sealer systems by using a brush, roller, squeegee, or sprayer. Easiest application can be achieved by spreading with a notched squeegee and back-rolling on spiked shoes. If two coats are needed, a second coat can be applied as soon as the first coat is dry enough to walk on. Thickness per coat is 95 square feet per gallon. MINIMUM 16MIL DFT REQUIRED TO MAINTAIN STATIC DISSIPATING PROPERTIES.

### **Safety Precautions:**

Prolonged or repeated exposure to epoxy materials may cause eye or skin irritation. If contact occurs, wash affected area with soap and water immediately. If discomfort continues seek medical attention. Always wear suitable protective clothing and use proper safety devices. See respective MSDS for complete details.

### **Clean-Up:**

All tools and equipment should be cleaned before material gels. Use Rez-Stone 1201 epoxy reducer.



Warranties: Hoover & Wells, Inc. warrants the quality of its Rez-Stone products, and takes responsibility only for furnishing specifications and recommendations for their proper installation. Hoover & Wells, Inc. hereby disclaims all other warranties expressed or implied, and any implied warranties of merchantability or fitness for a particular purpose. Hoover & Wells, Inc. shall have no liability to the Purchaser for any property damage, bodily injury, death or other loss arising out of possession or use of Rez-Stone products. Hoover & Wells, Inc. shall not be responsible for any claim resulting from failure to use its product other than the manner outlined with the instructions provided for use of the products. Under no circumstances shall Hoover & Wells, Inc. be liable for any damages or otherwise in excess of the purchase price. Any claim for breach of warranty shall be given to Hoover & Wells, Inc. in writing with 90 days of delivery or the claim shall be deemed waived. All information here is provided in good faith only as an aid to the Purchaser. Thus, the Seller does not guarantee the accuracy of the information and assume no liability for reliance thereof. Rez-Stone® is a registered trademark of Hoover & Wells, Inc.

**5078-C TYPICAL PROPERTIES AND SPECIFICATIONS**

Blended Viscosity	6,700 cps @ 70°F
Pot Life	20-25 Minutes @ 70°F
Tack Free, Recoat Time	6 Hour @ 70°F
Cured for Foot Traffic	12 Hours @ 70°F
Cured for Forklift Traffic	24 Hours @ 70°F
Color	Clear – Also available in all standard colors
Solids, Mixed	% by Weight 100± 2 % by Volume 100± 2
Shelf Life	Greater than one year in original unopened package
Storage	Dry, between 50°F and 90°F
Tensile Strength ASTM D-638	2,400 psi
Compressive Strength ASTM C-579	11,200 psi
Flexural Strength ASTM D-790	4,300 psi
Tensile Elongation	10%
Bond Strength	Greater than concrete
Surface Resistance ASTM F-150-89	<1x10 <sup>6</sup> Mega OHMS

**CHEMICAL RESISTANCE**

Rez-Stone 5078-C has good resistance to most common acids, alkali, fuels, grease, salts, and strong detergents. The following information is based on 24-hour soak testing at 20 mils. The information is correct to the best of our knowledge. A test area is always recommended to determine actual chemical resistance in critical situations.

Reagent	Affect
5% Acetic Acid	Unaffected
10% Sulfuric Acid	Discolored
5% Nitric Acid	Unaffected
10% Phosphoric Acid	Discolored
20% Ammonium Hydroxide	Unaffected
20% Sodium Hydroxide	Unaffected
Tri-Sodium Phosphate	Unaffected
Brake Fluid (Auto)	Slight Softening
Gasoline	Unaffected
A-1 Jet Fuel	Unaffected
MEK	Destroyed
Methyl Chloride	Destroyed
Mineral Spirits	Unaffected
Xylene	Slight Softening
Beer	Unaffected
Mustard	Unaffected
Milk	Unaffected
Urine	Unaffected
Whiskey	Unaffected
Vegetable Oil	Unaffected

Warranties: Hoover & Wells, Inc. warrants the quality of its Rez-Stone products, and takes responsibility only for furnishing specifications and recommendations for their proper installation. Hoover & Wells, Inc. hereby disclaims all other warranties expressed or implied, and any implied warranties of merchantability or fitness for a particular purpose. Hoover & Wells, Inc. shall have no liability to the Purchaser for any property damage, bodily injury, death or other loss arising out of possession or use of Rez-Stone products. Hoover & Wells, Inc. shall not be responsible for any claim resulting from failure to use its product other than the manner outlined with the instructions provided for use of the products. Under no circumstances shall Hoover & Wells, Inc. be liable for any damages or otherwise in excess of the purchase price. Any claim for breach of warranty shall be given to Hoover & Wells, Inc. in writing with 90 days of delivery or the claim shall be deemed waived. All information here is provided in good faith only as an aid to the Purchaser. Thus, the Seller does not guarantee the accuracy of the information and assume no liability for reliance thereof. Rez-Stone® is a registered trademark of Hoover & Wells, Inc.

