

REZSTONE

Epoxy Floor Systems

SPECIFICATIONS

9500 EPOXY FLOOR TOPPING SYSTEM

Description:

Rez-Stone 9500 is a three-component 100% solids epoxy-based mortar flooring system. Rez-Stone 9500 can be used where rapid strength gaining overlayment is required. When applied at 1/4" it is more impact, chemical, and wear-resistant than conventional floor systems. Typically recommended for economical leveling or resurfacing of concrete areas of floors subjected to heavy industrial use.

Advantages:

- ✓ Economical
- ✓ 100% solids, can be applied at any thickness when necessary
- ✓ Excellent chemical, impact, and abrasion-resistance
- ✓ Non-slip finishes available
- ✓ Seamless cove base available
- ✓ USDA compliant materials
- ✓ Solvent free
- ✓ No VOC's

Limitations:

- ✓ Substrate minimum temperature 50°F
- ✓ New concrete must be at least 28 days old
- ✓ Do not apply over wet substrate
- ✓ Expansion joints must be re-cut through topping

Coverage at Normal 1/4" Thickness:

Prime Coat	175 – 225 Square Feet per Gallon	Rez-Stone 5014 or 5017
Matrix Binder	25 Square Feet per Gallon	Rez-Stone 5014 or 5017
Matrix Aggregate	2 Pounds per Square Foot	Blended Aggregate
Chemical Resistant Topcoat	90 Square Feet per Gallon	Rez-Stone 5078

Surface Preparation:

Concrete surfaces must be clean and sound. Remove all dirt, laitance, grease, curing compounds, and other bond-inhibiting contaminants by shot blasting, scarification, or other approved mechanical methods.

Application:

After proper surface preparation, the concrete surface will be primed using Rez-Stone 5017 primer-binder with a heavy-duty medium nap roller. Lightly broadcast 1 pound per 5 square feet of blended aggregate into the wet primer to help trowel ability. (Note: Matrix may be placed immediately, but do not allow primer to cure for more than 24 hours before placement of overlay.) Blend proportioned amounts of Rez-Stone 5017 Part A and Part B for 3 minutes using mechanical agitation. Load proportioned matrix aggregate into a paddle or screw-type mortar mixer followed by the pre-blended 5017 binder. Mix for 1 minute. Place mixed material onto floor using a screed box or straight edge. Power-trowel the placed matrix for a smooth compacted finish. Allow matrix to cure for 8-10 hours or until tack-free. Once matrix has cured it should be lightly scraped with an ice spud or similar scraping tool and broom swept before topcoating. Roller-apply Rez-Stone 5078 100% solids epoxy topcoat at a rate of 90 square feet per gallon for a lightly-textured finish. If a non-slip finish is needed a silica or aluminum oxide aggregate may be incorporated into the topcoat.

Safety Precautions:

Prolonged or repeated exposure to epoxy materials may cause eye or skin irritation. If contact occurs, wash affected area with soap and water immediately. If discomfort continues seek medical attention. Always wear suitable protective clothing and use proper safety devices. See respective MSDS for complete details.

Clean-Up:

All tools and equipment should be cleaned before material gels. Use Rez-Stone 1201 epoxy reducer.



Warranties: Hoover & Wells, Inc. warrants the quality of its Rez-Stone products, and takes responsibility only for furnishing specifications and recommendations for their proper installation. Hoover & Wells, Inc. hereby disclaims all other warranties expressed or implied, and any implied warranties of merchantability or fitness for a particular purpose. Hoover & Wells, Inc. shall have no liability to the Purchaser for any property damage, bodily injury, death or other loss arising out of possession or use of Rez-Stone products. Hoover & Wells, Inc. shall not be responsible for any claim resulting from failure to use its product other than the manner outlined with the instructions provided for use of the products. Under no circumstances shall Hoover & Wells, Inc. be liable for any damages or otherwise in excess of the purchase price. Any claim for breach of warranty shall be given to Hoover & Wells, Inc. in writing with 90 days of delivery or the claim shall be deemed waived. All information here is provided in good faith only as an aid to the Purchaser. Thus, the Seller does not guarantee the accuracy of the information and assume no liability for reliance thereof. Rez-Stone® is a registered trademark of Hoover & Wells, Inc.

9500 TYPICAL PROPERTIES AND SPECIFICATIONS OF CURED SYSTEM

Working Time	30-35 minutes @ 70°F
Cure Time: Initial Set-for-Life Traffic	16 hours @ 70°F
Cure Time: Ultimate Cure	7 days @ 70°F
Compressive Strength ASTM C-579	11,000 psi
Tensile Strength ASTM C-307	1,890 psi
Flexural Strength ASTM C-580	4,500 psi
Shore "D" Hardness ASTM D-2240	85
Water Absorption ASTM C-413	0.2%
Percent Elongation ASTM D-638	0.2
Abrasion Resistance ASTM D-4060	0.1 gram
Moisture Vapor Permeability ASTM E96-80	0.06 perms
Thermal Shock Resistance ASTM C-884	Passes
Flammability ASTM D-635	Self-extinguishing
Flame Spread ASTM E-84	Class B
Static Coefficient of Friction ASTM C-1028	0.5 to 0.9 will vary with selected finish
Thermal Coefficient of Linear Expansion ASTM D-696	2.5×10^{-5} in/in/deg F
Impact Resistance MIL-D-3134F	No Indentation
Bond Strength ACI Committee 403/59-43	350 psi (100% concrete failure)
Electrical Resistivity, NFPA Bulletin #56A	Non-conductive
Color	Available in all standard colors

CHEMICAL RESISTANCE

Rez-Stone 9500 has good resistance to most common acids, alkali, fuels, grease, salts, and strong detergents. The following information is based on 7-day soak testing with 5017 binder and 5078 topcoat. The information is correct to the best of our knowledge. A test patch is always recommended to determine actual chemical resistance in critical situations.

Reagent	Affect
5% Acetic Acid	Unaffected
10% Sulfuric Acid	Discolored
5% Nitric Acid	Unaffected
10% Nitric Acid	Discolored
10% Phosphoric Acid	Discolored
10% Hydrochloric Acid	Unaffected
20% Ammonium Hydroxide	Unaffected
20% Sodium Hydroxide	Unaffected
10% Tri-Sodium Phosphate	Unaffected
Brake Fluid (Auto)	Softened
Gasoline	Unaffected
Jet Fuel JP4	Unaffected
Ethyl Alcohol	Softened
MEK	Destroyed
Methyl Chloride	Destroyed
Mineral Spirits	Unaffected
Motor Oil	Unaffected
Xylene	Softened
Soda Pop	Unaffected
Beer	Unaffected
Cola Syrup	Unaffected
Mustard	Unaffected
Milk	Unaffected
Urine	Unaffected
Whiskey	Unaffected
Vegetable Oil	Unaffected
Distilled Water	Unaffected
Salt Water	Unaffected

Warranties: Hoover & Wells, Inc. warrants the quality of its Rez-Stone products, and takes responsibility only for furnishing specifications and recommendations for their proper installation. Hoover & Wells, Inc. hereby disclaims all other warranties expressed or implied, and any implied warranties of merchantability or fitness for a particular purpose. Hoover & Wells, Inc. shall have no liability to the Purchaser for any property damage, bodily injury, death or other loss arising out of possession or use of Rez-Stone products. Hoover & Wells, Inc. shall not be responsible for any claim resulting from failure to use its product other than the manner outlined with the instructions provided for use of the products. Under no circumstances shall Hoover & Wells, Inc. be liable for any damages or otherwise in excess of the purchase price. Any claim for breach of warranty shall be given to Hoover & Wells, Inc. in writing with 90 days of delivery or the claim shall be deemed waived. All information here is provided in good faith only as an aid to the Purchaser. Thus, the Seller does not guarantee the accuracy of the information and assume no liability for reliance thereof. Rez-Stone® is a registered trademark of Hoover & Wells, Inc.

