

REZSTONE

Epoxy Floor Systems

TECHNICAL DATA

2500 EPOXY PATCH KIT 2501 FAST-SET PATCH KIT 2502 SEMI-RIGID PATCH KIT

Description:

Rez-Stone 2500, 2501, and 22502 Epoxy Crack Repair Kits are premeasured, solvent-free, rapid-strength gaining materials. They are for industrial use to repair cracks, holes, and spalled areas of concrete less than ¼" deep. Uniquely designed to a butter-like consistency, Rez-Stone Crack Repair material will not run or sag. Excellent for repairs directly over concrete or within Rez-Stone Floor Systems. They are available in regular, flexible, and fast-setting formulations for normal and adverse conditions.

Advantages:

- ✓ Rapid-strength gain
- ✓ Non-sagging
- ✓ Non-flammable 100% solids epoxy
- ✓ Premeasured kits
- ✓ Featheredge or apply up to ¼" thick

Limitations:

- ✓ Substrate minimum temperature 50°F for 2500 & 2502 or 35°F for 2501
- ✓ New concrete must be at least 28 days old
- ✓ Do not apply over wet substrate

Packaging & Coverage:

Unit Size: 3 quart units and 3 gallon units (packaged in kit form for easy mixing).

Average coverage for cracks or joints ¼" deep x ¼" wide: 1 gallon will fill 308 lineal feet. One 3 quart unit will fill 230 lineal feet.

Surface Preparation:

Concrete surfaces must be clean and sound. Remove all dirt, laitance, grease, wax, curing compounds, and other bond-inhibiting contaminants by shot blasting, scarification, or other approved mechanical methods.

Mixing:

Temperature of material should be the same as ambient air temperature at time of mixing for best application properties. Pour entire contents of Part B into Part A container; scrape the sides to remove all of the Part B component. Mix for 3 minutes with mechanical agitation. Mix to a uniform blend working the sides and bottom of the can to ensure all material has been mixed.

Application:

Priming is not necessary but is recommended when material will be subjected to extreme heat or cold. Place mixed material with a hand trowel or putty knife. Finish with the same tools by pressing firmly to the substrate and strike off clean. Ambient air and surface temperature will affect both the pot life and cure times of installed material. As a rule of thumb, mixed material should be placed and finished within 10 to 15 minutes of mixing. Once cured, Rez-Stone 2500 and 2502 may be coated over directly. Rez-Stone 2501 may need additional surface preparation before over coating.

Safety Precautions:

Prolonged or repeated exposure to epoxy materials may cause eye or skin irritation. If contact occurs, wash affected area with soap and water immediately. If discomfort continues seek medical attention. Always wear suitable protective clothing and use proper safety devices. See respective MSDS for complete details.

Clean-Up:

All tools and equipment should be cleaned before material gels. Use Rez-Stone 1201 epoxy reducer.



Warranties: Hoover & Wells, Inc. warrants the quality of its Rez-Stone products, and takes responsibility only for furnishing specifications and recommendations for their proper installation. Hoover & Wells, Inc. hereby disclaims all other warranties expressed or implied, and any implied warranties of merchantability or fitness for a particular purpose. Hoover & Wells, Inc. shall have no liability to the Purchaser for any property damage, bodily injury, death or other loss arising out of possession or use of Rez-Stone products. Hoover & Wells, Inc. shall not be responsible for any claim resulting from failure to use its product other than the manner outlined with the instructions provided for use of the products. Under no circumstances shall Hoover & Wells, Inc. be liable for any damages or otherwise in excess of the purchase price. Any claim for breach of warranty shall be given to Hoover & Wells, Inc. in writing with 90 days of delivery or the claim shall be deemed waived. All information here is provided in good faith only as an aid to the Purchaser. Thus, the Seller does not guarantee the accuracy of the information and assume no liability for reliance thereof. Rez-Stone® is a registered trademark of Hoover & Wells, Inc.

TYPICAL PROPERTIES AND SPECIFICATIONS

	2500	2501	2502
Compressive Strength ASTM D-695	≥10,000 psi	≥10,000 psi	≥6,300 psi
Tensile Strength ASTM D-638	5,500 psi	9,000 psi	3,500 psi
Tensile Elongation	10%	6%	50%
Flexural Strength	9,400 psi	14,000 psi	5,000 psi
Bond Strength	Greater than concrete		
Standard Color	Concrete (available in all standard colors)		
Shelf Life	One year in original package, unopened		
Storage	Dry, between 50°F and 90°F		

CURE TIMES

Temperature	2500 & 2602		2501
	Pot Life	Truck Traffic	Pot Life/Truck Traffic
40°F	Not Recommended		65 minutes/20 hours
50°F	60 minutes	20 hours	35 minutes/10 hours
60°F	40 minutes	10 hours	20 minutes/6 hours
70°F	25 minutes	8 hours	10 minutes/4 hours
80°F	10 minutes	5 hours	Not Recommended

Actual cure time may vary due to patch thickness and length of mixing time. Best working and curing properties are obtained by conditioning material to 60°F - 80°F for 2610 and 2612, 35°F - 60°F for 2611.

Warranties: Hoover & Wells, Inc. warrants the quality of its Rez-Stone products, and takes responsibility only for furnishing specifications and recommendations for their proper installation. Hoover & Wells, Inc. hereby disclaims all other warranties expressed or implied, and any implied warranties of merchantability or fitness for a particular purpose. Hoover & Wells, Inc. shall have no liability to the Purchaser for any property damage, bodily injury, death or other loss arising out of possession or use of Rez-Stone products. Hoover & Wells, Inc. shall not be responsible for any claim resulting from failure to use its product other than the manner outlined with the instructions provided for use of the products. Under no circumstances shall Hoover & Wells, Inc. be liable for any damages or otherwise in excess of the purchase price. Any claim for breach of warranty shall be given to Hoover & Wells, Inc. in writing with 90 days of delivery or the claim shall be deemed waived. All information here is provided in good faith only as an aid to the Purchaser. Thus, the Seller does not guarantee the accuracy of the information and assume no liability for reliance thereof. Rez-Stone® is a registered trademark of Hoover & Wells, Inc.

